


System Bulletin

# StoTherm® ci with Sto Strike Defense

Decorative cladding with continuous insulation and StoGuard® Air and Water-resistive Barrier combined with Sto Strike Defense for high impact and puncture resistance



Substrate: Glass Mat Gypsum sheathing in compliance with ASTM C 1177, Exterior or Exposure I wood-based sheathing (plywood or OSB), cement board in compliance with ASTM C1325, or code compliant concrete, concrete masonry or portland cement plaster, existing structurally sound, uncoated brick or other masonry wall construction.

- |    |  |
|----|--|
| 1) | Air Barrier and Water-resistive Barrier: StoGuard  |
| 2) | Adhesive options: Sto TurboStick®, Sto BTS® Plus, Sto BTS Xtra, Sto Primer/Adhesive-B, or Sto Primer/Adhesive  |
| 3) | Insulation: Sto EPS Insulation Board   |
| 4) | Reinforcement: Sto Armor Mat or Sto Amor Mat XX (embedded in Sto base coat)  |
| 5) | Base Coat options: Sto BTS Plus, Sto BTS Xtra, Sto RFP, StoArmat Classic Plus, Sto Primer/Adhesive-B, or Sto Primer/Adhesive   |
| 6) | Sto Strike Defense: <ul style="list-style-type: none"> <li>• Sto Mesh embedded in StoArmat Classic Plus</li> <li>• 2<sup>nd</sup> coat, and 3<sup>rd</sup> coat (if needed) of StoArmat Classic Plus to achieve minimum 3/16-in (4.0mm) thickness</li> </ul> |
| 7) | StoCast Wood Adhesive  |
| 8) | Finish: choose among, <ul style="list-style-type: none"> <li>• Sto Textured Finishes</li> <li>• StoCast Finishes (StoCast Wood shown)</li> <li>• Sto Signature and Sto Specialty Finishes</li> </ul>   |

System Accessory: StoSeal STPE Sealant for use as an exterior weather seal around wall penetrations, at dynamic joints in wall construction, and as an interior air seal for air barrier continuity

### System Description

StoTherm ci with Sto Strike Defense is a decorative and protective exterior wall cladding that combines superior air and weather tightness with excellent thermal performance and durability. It incorporates continuous exterior insulation and StoGuard Air and Water-resistive Barrier with Sto Strike Defense for high impact and puncture resistance.

### Uses

StoTherm ci with Sto Strike Defense can be used in residential or commercial wall construction where energy efficiency, superior aesthetics, and air and moisture control are essential in the climate extremes of North America.

Features	Benefits
Design versatility	Aesthetic and curb appeal easy to achieve
Continuous exterior insulation, no mechanical fasteners	Energy efficient, reduced heating and cooling costs
Lightweight	Reduced structural costs
Continuous air and water-resistive barrier	Protects against mold and moisture problems
Outstanding resistance to blunt and sharp object impact	Protects new and existing buildings from high energy impact and mitigates damage caused by woodpeckers

### Properties

Weight (not including sheathing and frame)	< 3.5 psf (17.1 kg/m <sup>2</sup> )
Thickness (insulation)	1 to 12 inches (25 – 305 mm)
R-value (not including sheathing and frame)	3.6 – 43.2 ft <sup>2</sup> •h•°F / Btu (0.63 – 7.60 m <sup>2</sup> •K / W)
Wind Load Resistance	Tested up to ± 188 psf (9.00 kPa)
Compliance	<ul style="list-style-type: none"> <li>• IBC, IRC, IECC-2015, 2018</li> <li>• ASHRAE 90.1-2019</li> </ul>
Construction Types and Fire Resistance	<ul style="list-style-type: none"> <li>• I-V, NFPA 285 tested for types I-IV</li> <li>• ASTM E119 tested for 1&amp;2 hour walls</li> <li>• Refer to ICC ESR-1748</li> </ul>

### Warranty

15 year Limited Warranty

### Maintenance

Requires periodic cleaning to maintain appearance, repair to cracks and impact damage if they occur, recoating to enhance appearance of weathered finish. Sealants and other façade components must be maintained to prevent water infiltration.

System Bulletin

# StoTherm® ci with Sto Strike Defense

Decorative cladding with continuous insulation and StoGuard® Air and Water-resistive Barrier combined with Sto Strike Defense for high impact and puncture resistance

Limitations
Minimum insulation board thickness 1-in (25 mm). Maximum insulation board thickness 12-in (305 mm), 6-in (152mm) if StoCast Finishes are used on Types I-IV (Noncombustible) construction. Refer to ICC ESR-1748 for detailed information on allowable products.
Fire resistance rated assemblies limited to 6-in (152 mm) maximum insulation board thickness, 4-in (102mm) if StoCast Finishes are used. Refer to ICC ESR-1748 for detailed information on allowable products. Listing of StoArmat Classic Plus in fire resistance-rated assemblies is pending.
Do not use on interior walls. A thermal barrier is required (typically minimum ½-in [13mm] gypsum wallboard) to separate the insulation board from the interior
Structural back-up wall must be level to ¼ inch in 10 ft (6mm in 3.0m)
Wind load resistance: ± 188 psf (9.00 kPa) ultimate loads achieved. Ultimate wind load resistance also depends on sheathing, sheathing attachment, and stiffness of supporting construction. Design for maximum allowable deflection of L/240.
Impact resistance: supplemental reinforcing mesh layers, cement board overlay or other design adjustments may be prudent for areas adjacent to heavy pedestrian traffic or other areas of high impact or abuse. Refer to Sto Guide Details.
For use on vertical above grade walls only. Do not use below grade or on roofs or roof-like surfaces.
Insulation material is flammable. Keep away from flame, ignition sources, high heat, and temperatures in excess of 165°F [74° C]).
Dark finish colors with LRV (Light Reflectance Value) < 20 are not recommended.
Air Barrier, insulation board, and base coat materials are not intended for prolonged weather exposure. Allow 180 days maximum between application of air and water-resistive barrier and insulation board.
Refer to specific component product bulletins and packaging for other limitations that may apply involving use, handling, and storage of component materials.

Sustainable Design	
<b>Air Quality and VOC Compliance</b>	
All finish coatings, adhesives, air barrier detail components and coatings meet US EPA (40 CFR 59) and South Coats AQMD (Rule 1113) emission standards for Building Envelope Coatings: VOC less than 50 g/L.	
<b>Sustainability</b>	
The system has high potential for LEED and other sustainability program credits based on efficient and effective use of a continuous air barrier and continuous exterior insulation and the resulting reductions in energy use and greenhouse gas emissions. The use of light weight metal studs and light weight finishes has positive impacts on life cycle energy use by reducing dead loads and structural support requirements when compared to mass wall and full thickness/weight veneer units.	
<b>Regulatory Compliance and Standards Testing</b>	
ICC ESR No. 1748 covering StoTherm ci	Complies with 2015 and 2018 IBC, IRC and IECC
ICC ESR No. 1233 covering StoGuard	Complies with 2015 and 2018 IBC, IRC and IECC
ASHRAE 90.1-2019 <sup>1</sup>	Complies with Section 5, Building Envelope, air barrier and continuous insulation requirements
ASTM E 2357 <sup>2</sup>	Air and Water-resistive Barrier meets air leakage resistance of ≤ 0.04 cfm/ft <sup>2</sup> at 1.57 psf (0.2 L/s•m <sup>2</sup> at 75 Pa)
NFPA 285 <sup>3</sup>	Meets flame propagation criteria for use on Types I, II, III, IV construction with up to 12-in (305 mm) of Sto EPS insulation board, 6-in (152mm) for StoCast Finishes (refer to ICC-ESR 1748 for details)
ASTM E 119 <sup>4</sup>	Meets requirements for use over fire-resistance-rated wall assemblies with maximum 6-in (152mm) thick of Sto EPS insulation board, 4-in (102mm) for StoCast Finishes (refer to ICC ESR-1748 for details).

1. Energy Standard for Buildings Except Low-Rise Residential Buildings
2. Standard Test Method for Determining Air Leakage Rate of Air Barrier Assemblies
3. Standard Fire Test Method for Evaluation of Fire Propagation Characteristics of Exterior Non-Load-Bearing Wall Assemblies Containing Combustible Components
4. Standard Test Methods for Fire Test of Building Construction and Materials

<p><b>Sto Corp.</b> 3800 Camp Creek Parkway Building 1400, Suite 120 Atlanta, GA 30331</p> <p>Tel: 404-346-3666 Toll Free: 1-800-221-2397 Fax: 404 346-3119 <a href="http://www.stocorp.com">www.stocorp.com</a></p>	<p><b>SB-5200</b> Revision: 002 Date: 08/2024</p>	<p style="text-align: center;"><b>Attention</b></p> <p>Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. <b>STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.</b> For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, <a href="http://www.stocorp.com">www.stocorp.com</a>.</p>
--	---	--